





Rev	AWO #	Description	Date	Appr
-		RELEASED	12/29/04	

APPROVED: \_\_\_\_\_  
 DATE: \_\_\_\_\_ TITLE: \_\_\_\_\_



**SPECIFICATIONS:**

Material: Insulator: PBT, Glass filled, rated UL 94V-0  
 Insulator color: Black  
 Contacts: Brass  
 Plating: Tin over Copper underplate overall

Electrical: Operating voltage: 250 VAC max.  
 Current rating: 1 Amp max.

Operating resistance: 20 mohms max. initial  
 Dielectric withstanding voltage: 1,000 VAC for 1 minute  
 Temperature Rating: Operating temperature: -40°C to +105°C

Positions: 8, 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60, 64  
 A = .079 [2.00] x No. of Spaces + .362 [9.20]  
 B = .079 [2.00] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED	
INCHES	± .10
HOLE	± .015
ØXX	± .015
ØXXX	± .010
APPROVALS	DATE

**ADAM TECH**  
 909 Rahway Avenue, Union, NJ 07083  
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .079 [2.00] BOX HEADER, RIGHT ANGLE, TIN PLATED, STANDARD SOLDER TAIL

DRAWN	SS	12/29/04	SIZE	PART NO.	REV.
CHECKED			X	2BHR-XX-HTA	-
APPROVED			REF:	SCALE: NTS	SHEET 1 OF 1