




Rev	AWO #	Description	Date	Appr
-		RELEASED	4/8/05	

APPROVED: _____
 DATE: _____ TITLE: _____



Positions: 2 thru 15
 A = .079 [2.00] x No. of Positions
 B = .079 [2.00] x No. of Spaces

SPECIFICATIONS:
 Material:
 Insulator: Nylon 66, rated UL 94V-0
 Insulator color: Brown
 Electrical:
 Operating voltage: 250 VAC max
 Current rating: 1 Amp max
 Insulation resistance: 1,000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 800 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -25°C to +85°C
 Environmental:
 Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		Holes .10 ±.010 .020 ±.010 .015 ±.010	
DRAWN: SS		DATE: 4/8/05	
CHECKED:		SIZE: X	
APPROVED:		PART NO.: ZCH-2XX	
TITLE 079 [2.00] CRIMP HOUSING LOW PROFILE, DUAL POLARIZED		SCALE: NTS SHEET 1 OF 1	
ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710		REV: -	