Rev	AWO #	Description	Date	Appr
-		RELEASED	9/17/10	

APPROVED: _____

DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT
(TOP VIEW)

MODEL NO	ASJ-4-3S	ASJ-4-3B
SCHEMATIC		

SPECIFICATIONS:
Material:
Insulator: PA66, rated UL 94V-0
Insulator color: Black
Bushing: Brass , Nickel plated
Contacts: Phosphor Bronze, Tin plated.
Electrical:
Rated Voltage & Current: DC 30V, 0.5A
Contact resistance: 30 mohms max.
Insulation resistance: 100 Mohms min.
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: -25°C to +70°C
Environmental:
Lead free, RoHS compliant.
Recommended soldering temp: 235°C for 5 sec.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	9/17/10
CHECKED	VW	9/17/10
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
2.5MM STEREO PHONE JACK

SIZE	PART NO.	REV.
X	ASJ-4-XX	-

REF: S00030C | SCALE: NTS | SHEET 1 OF 1