Rev	AWO #	Description	Date	Appr
-		RELEASED	12/10/04	

APPROVED: _____

DATE: _____ TITLE: _____







PCB LAYOUT

CONTACT FORM	ASJ-6-02	ASJ-6-03	ASJ-6-3A	ASJ-6-4A	ASJ-6-4B	ASJ-6-05
SCHEMATIC						

SPECIFICATIONS:
Material:
Insulator: PBT, Glass reinforced, rated UL 94V-0
Insulator color: Black
Contacts: Copper Alloy
Plating:
Tin over Copper underplate
Electrical:
Operating voltage: 12 VDC max.
Current rating: 1 Amp max.
Contact resistance: 30 mohms max. initial
Insulation resistance: 100 Mohms min.
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
Operating temperature: -65°C to +125°C

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	SS	10/4/04
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: STEREO JACK

SIZE	PART NO.	REV.
X	ASJ-6-XX	-

REF: | SCALE: NTS | SHEET 1 OF 1