

6

5

4

3

2



1

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/03/09	



APPROVED: _____

DATE: _____ TITLE: _____

D



C



B

SPECIFICATIONS:

Material:

Insulator: PBT, glass reinforced, rated UL 94V-0

Insulator color: Black

Contacts: Copper Alloy

Shell: Steel, Tin plated

Hardware: Brass, Nickel plated

Plating:

Gold flash over Nickel underplate overall.

Electrical:

Operating voltage: 250 VAC max

Current rating: 5 Amps max

Contact resistance: 20 mohms max

Insulation resistance: 1,000 Mohms min

Dielectric withstanding voltage: 1,000 VAC for 1 minute

Environmental:

Lead free, RoHS compliant

Recommended soldering temp: 235°C for 5 seconds

6

5

4

3

2

1

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
D-SUB PLUG, R/A, MACHINED CONTACT
WITHOUT BRACKET, .120" NON-THREADED HOLES

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]	
TOLERANCES: EXCEPT AS NOTED	
INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXXX ± .015
.XXX ± .015	ØXXX ± .010
APPROVALS	DATE
DRAWN DY	11/03/09
CHECKED	
APPROVED	

REF: S00087T	SCALE: NTS	SHEET 1 OF 1
SIZE X	PART NO. DD50-PH-G1C	REV. -

