



Rev	AWO #	Description	Date	Appr
-	9427	RELEASED	3/20/09	

APPROVED: _____
 DATE: _____ TITLE: _____



SPECIFICATIONS:

Material:
 Insulator: PA66, rated UL 94V-0
 Insulator color: Green
 Contact: Copper, Tin plated.
 Electrical:
 Operation voltage: 300 VAC max
 Current rating: 30 Amps max per Pole
 Contact resistance: 20 mohms max
 Insulation resistance: 500 Mohms min @ DC500V
 Dielectric withstanding voltage: 1600 VAC for 1 minute
 Environmental:
 Operating temperature: -40°C to +105°C
 Lead free, RoHS compliant.
 Recommended soldering temp: 235°C for 5 sec.



ADAM TECH

909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: TERMINAL BLOCK, SOCKETS FOR PLUGGABLE,
 RIGHT ANGLE, 7.62MM PITCH

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MM	
TOLERANCES: EXCEPT AS NOTED	
.X ± .10	ØX ± .10
.XX ± .020	ØXXX ± .015
.XXX ± .015	ØXXX ± .010
APPROVALS	DATE
DRAWN DY	3/20/09
CHECKED	
APPROVED	

REF: X	SIZE: X	PART NO.: EB43-XX-G	REV: -
S00024T	SCALE: NTS	SHEET 1 OF 1	