



ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

SPECIFICATIONS:
 Material: Hi-temp thermoplastic, UL 94V-0
 Housing color: Black
 Contact: Copper Alloy
 Shield: Copper Alloy, Nickel plated
 Plating: 15u" Gold over Nickel underplate on contact area, Tin over Copper underplate on tails.
 Electrical:
 Voltage rating: 40V
 Current rating: 0.5A
 Dielectric strength: 300VAC for 1 minute min.
 Insulation resistance: 100 Megohm min.
 Contact resistance: 10 mohms max.
 Environmental:
 Lead free, RoHS Compliant
 Recommended soldering temp: 260°C for 5 seconds.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MM
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXX ± .015
.XXX ± .015	ØXXX ± .010

APPROVALS: _____ DATE: _____

DRAWN: DY 6/08/10
 CHECKED: _____
 APPROVED: _____

TITLE: **HDMI CONNECTOR, 19P, VERTICAL, SMT**
 SIZE: X
 PART NO.: **HDMI-S-V-01-SMT-MF-15-KT**
 REF: S00015C
 SCALE: NTS
 SHEET 1 OF 1