





Rev	AWO #	Description	Date	Appr
-		RELEASED	1/6/05	

APPROVED: _____
 DATE: _____ TITLE: _____



SPECIFICATIONS:
 Material: Nylon 6T, rated UL 94V-0
 Insulator color: Black
 Contacts: Brass

Plating:
 Gold flash over Nickel underplate on contact area, Tin over Copper underplate on tails

Electrical:
 Operating voltage: 250 VAC max.
 Current rating: 1 Amp max.
 Contact resistance: 20 mohms max. initial
 Insulation resistance: 5,000 Mohms min.
 Dielectric withstanding voltage: 1,000 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -40°C to +105°C

Positions: 01 thru 32
 A = .050 [1.27] x No. of Positions Per Row
 B = .050 [1.27] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ϕ XX ± .10
.XX ± .020	ϕ XXX ± .015
.XXX ± .015	ϕ XXX ± .010

APPROVALS

DATE	DATE

ADAM TECH
 909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

DRAWN	SS	1/6/05	SIZE	PART NO.	REV.
CHECKED			X	HPH1-A-XX-SGA	
APPROVED			REF:	SCALE: MTS	SHEET 1 OF 1

6 5 4 3 2 1