




Rev	AWO #	Description	Date	Appr
-	V1545	RELEASED	2/10/11	

APPROVED: _____
 DATE: _____ TITLE: _____



RECOMMENDED PCB LAYOUT

SPECIFICATIONS:

- Material: Insulator: Thermoplastic, rated UL 94V-0
- Insulator color: Black
- Contacts: Brass
- Plating: Gold flash over Nickel underplate overall.
- Electrical: Current rating: 1 Amp max.
- Contact resistance: 20 mohms max. @ DC 100mA
- Insulation resistance: 5,000 Mohms min. @ DC 500V
- Dielectric withstanding voltage: 500 VAC for 1 minute
- Temperature Rating: Operating temperature: -55°C to +105°C
- Environmental: Lead free, RoHS compliant
- Recommended soldering temp: 235°C for 5 seconds



ADAM TECH

909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .050 [1.27] DUAL ROW PIN HEADER

GOLD PLATED

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]	
TOLERANCES: EXCEPT AS NOTED	
INCHES	HOLES
.X ± .10	ØX ± .10
.XX ± .020	ØXX ± .015
.XXX ± .015	ØXXX ± .010
APPROVALS	
DRAWN	DATE
DY	2/10/11
CHECKED	
APPROVED	

SIZE	PART NO.	REV.
X	HPH2-A-70-UA-V1545	-
REF:	S00059T	
SCALE:	NTS	
SHEET	1 OF 1	

6 5 4 3 2 1