





Rev	AWO #	Description	Date	Appr
-		RELEASED	1/10/05	

APPROVED: _____
 DATE: _____ TITLE: _____



PCB LAYOUT



SPECIFICATIONS:

Material: Hi-temp thermoplastic, rated UL 94V-0
 Insulator color: Black
 Contacts: Brass
 Plating: Gold flash over Nickel underplate overall
 Electrical:
 Operating voltage: 250 VAC max.
 Current rating: 1 Amp max.
 Contact resistance: 20 mohms max. initial
 Insulation resistance: 5,000 Mohms min.
 Dielectric withstanding voltage: 1,000 VAC for 1 minute
 Temperature Rating:
 Operating temperature: -40°C to +105°C
 Environmental:
 Lead free, RoHS compliant.
 Recommended soldering temp: 260°C for 5 sec.

Positions: 10 thru 100
 A = .050 [1.27] x No. of Spaces + .168 [4.27]
 B = .050 [1.27] x No. of Spaces + .074 [1.87]
 C = .050 [1.27] x No. of Spaces
 D = .050 [1.27] x No. of Spaces + .120 [3.05]

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X ± .10	ØXX ± .10
.XX ± .020	ØXXX ± .015
.XXX ± .015	ØXXXX ± .010

APPROVALS

DATE	DATE

DRAWN	SS	1/10/05
CHECKED	AY	7/28/10
APPROVED		

ADAM TECH
 909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

SIZE	PART NO.	REV.
X	HSH-XX-G-SMT	-

TITLE: .050 [1.27] SHROUDED HEADER, SMT
 VERTICAL
 REF: S00039T SCALE: NTS SHEET 1 OF 1

