Rev	AWO #	Description	Date	Appr
-		RELEASED	10/16/09	

APPROVED: _____

DATE: _____ TITLE: _____





SECTION:A–A



DETAIL:B
SCALE 2:1











RECOMMENDED PCB LAYOUT(TOLERANCE:0.05)
COMPONENT SIDE





SECTION:C–C



SECTION:D–D

SPECIFICATIONS:
Material:
Housing: LCP, rated UL 94V–0,, Black
Contact: Copper Alloy
Shell: Brass, nickel plated
Plating:
15u" Gold over Nickel underplate overall
Electrical:
Operating voltage: 40 VAC
Current rating: 0.5 Amps min
Withstanding Voltage: 500V AC for 1 minute
Insulation Resistance: 100M ohms min.
Contact Resistance: 30 ohms max.
Mechanical:
Terminal Retention Force: 0.2Kgf Min.
Temperature Rating:
Operating temperature: −25°C to +85°C
Environmetal:
Lead free, RoHS compliant.
Recommended soldering temp: 260°C for 5 sec.

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MM
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	DY	10/16/09
CHECKED		
APPROVED		

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE: MINI DISPLAY PORT RECEPTACLE, R/A, DIP TYPE, 20 PIN, GOLD PLATED

SIZE	PART NO.	REV.
X	MDPC-S-RA	-

REF: S00015C | SCALE: NTS | SHEET 1 OF 1