| Rev | AWO # | Description | Date | Appr |
|---|---|---|---|---|
| - | 11303 | RELEASED | 4/26/11 | |

APPROVED: _____

DATE: _____ TITLE: _____













RECOMMENDED PCB LAYOUT (TOP VIEW)

SPECIFICATIONS:
Material:
Insulator: Thermoplastic, rated UL 94V-0
Insulator color: Black
Contacts: Copper Alloy
Shield: Brass, Nickel plated
Contact Plating:
Gold Flash over Nickel underplate on contact area,
Tin over Copper underplate on tails
(See chart for thickness).
Electrical:
Operating voltage: 150 VAC max
Current rating: 1.5 Amps max
Contact Resistance: 20 mohms max. initial
Insulation resistance: 500 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1000 VAC for 1 minut
Temperature Rating:
Operating temperature: -40°C to +85°C
Environmental:
Lead free, RoHS compliant.
Recommended soldering temp: 235°C for 5 sec.

RoHS COMPLIANT

| X | PLATING |
|---|---|
| 0 | 15 µin Gold |
| 1 | 30 µin Gold |
| 2 | 50 µin Gold |

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

| INCHES | | HOLES | |
|---|---|---|---|
| .X | ± .10 | Ø.X | ±.10 |
| .XX | ± .020 | Ø.XX | ±.015 |
| .XXX | ± .015 | Ø.XXX | ±.010 |

| APPROVALS | | DATE |
|---|---|---|
| DRAWN | DY | 4/26/11 |
| CHECKED | | |
| APPROVED | | |


**ADAM TECH**
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710


TITLE: MODULAR JACK GANGED, 4 PORT, 8P8C
W / LED1 ORN/GRN, LED2 ORN/GRN

| SIZE | PART NO. | REV. |
|---|---|---|
| X | MTJG-4-88SX1-FSP-PG-LI-M50 | - |

REF: S00005C | SCALE: NTS | SHEET 1 OF 2